Printed on: 2025-Apr-10





# 3M<sup>™</sup> Silicone Spray, low VOC 60%, 24 floz

Part Number: 3M-SIL-LUB-LOWVOC-24OZ

3M™ Silicone Spray, Low VOC 60%, 24 fl. oz.

Lubricant with a Low VOC silicone base release agent suitable for industrial lubrication applications.

# **Product Description**

3M™ Silicone Lubricant is ideal for lubricating machinery and moving parts. It eliminates squeaks caused by friction, prevents sticking and freezing, and protects against rust. It can also aid in the prevention of glues, wax, inks and paints build up.



Printed on: 2025-Apr-

10

# **Technical Documents**

3M<sup>TM</sup> Silicone Spray - CA 05/24/18



# Safety Data Sheet

Copyright, 2018, 3M Company

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 26-7363-0 Version Number: Issue Date: 05/24/18 Supercedes Date: 07/01/16

# **SECTION 1: Identification**

# 1.1. Product identifier

3M™ Silicone Spray - CA

### Product Identification Numbers

62-4699-4930-9, 62-4699-4935-8

#### 1.2. Recommended use and restrictions on use

### Recommended use

Lubricant, Industrial use

# 1.3. Supplier's details MANUFACTURER:

Industrial Adhesives and Tapes Division 3M Center, St. Paul, MN 55144-1000, USA 1-888-3M HELPS (1-888-364-3577) ADDRESS: Telephone:

1.4. Emergency telephone number 1-800-364-3577 or (651) 737-6501 (24 hours)

# **SECTION 2: Hazard identification**

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

# 2.1. Hazard classification

Flammable Aerosol: Category 1. Gas Under Pressure: Liquefied gas. Serious Eye Damage/Irritation: Category 2A. Skin Corrosion/Irritation: Category 2. Aspiration Hazard: Category 1. Simple Asphyxiant.

Specific Target Organ Toxicity (single exposure): Category 1 Specific Target Organ Toxicity (single exposure): Category 3

### 2.2. Label elements

Page 1 of 12

View this product online at https://marathonhardware.com/pd/3M-SIL-LUB-LOWVOC-24OZ

Pag	e	3	/	3