



# **Top Stays Lift System 580-1250PF Light Weight**

Part Number: 105-SQ00AL

DTC Top Stays SQ Soft-Close Lift System, 580-1250 PF, Light Weight

This hinge-less lift system from DTC is the perfect solution for upper cabinets with flap doors. Not sure which one to order? <u>Try our easy-to-use Power Factor Calculator.</u>

Adjustment Type	3-Way
Angle	107
Application Type	Flap Door
Closing Type	Soft-Close
Door Height Range	250 to 500 mm
Force	L (Light)
Min. Cabinet Depth	240mm (9-1/2")
Opening Action	Progressive
Power Factor Range	580 - 1250

#### **Product Description**

Attractive design and absolute functionality are the two most important aspects in today's kitchen. The Top Stays lift system offer just that through an inconspicuous look and a rugged, yet customizable design. The hinge-less lift system is an optimal upper cabinet solution for saving space and increasing access to multiple upper cabinets simultaneously.

Learn more about Top Stays

### **Product Advantages**

- 3 mechanism kits cover most common doors
- Stays open at any desired angle
- · Opening angle and closing speed adjustments
- · 3-way door gap position adjustments
- · Integrated Infinity Soft-Close
- Certified for 60,000 cycles

How to Order? Calculate your Power Factor:



### **Important Information**

- Cabinet Width: Supports up to 1200mm (47 1/4")
- Cabinet Height Range: 250 500mm (9 7/8 –19 3/4")
- Door Thickness: 16-28mm (5/8 1 1/8")
- 107° door opening with optional restrictors

## **Product Application**

Perfect movement starts with correct power factor specific to your door's weight and height. If two factors align, we recommend to move up to the next strength or do a trial.

Top-Stays Power Factor Formula: Power Factor = Overall Cabinet Height (mm) x Door Weight (kg, including 2x weight of handle)

Calculate your Power Factor:



#### **Technical Documents**



View this product online at https://marathonhardware.com/pd/105-SQ00AL

Pag	le	4	/	4