



Adhesive & Activator Solo Kit

Part Number: F2P10SOLO

2P-10 Adhesive & Activator Kit

Two-Part Ten-Second (2P10) Solo Kit including 2 oz Adhesive and 12 oz Activator aerosol can.

<div>
</div>

Product Description

This is part of the FastCap 2P-10 Adhesive program. As a two-part 10-second adhesive, just apply the adhesive and then spray the activator. This will enable anything to stick for a strong, permanent bond.

Product Advantages

- · Speed and strength
- 10 seconds to bond
- Start sanding within 60 seconds
- Dries crystal clear
- 4000 PSI tensile and sheer
- Breaks the wood, not the glue!

Included Products

This starter kit includes a 12 oz. Activator aerosol spray can and a 2 oz. bottle of Thick purpose Adhesive.

Product Application

Apply adhesive to your material and then spray the activator. Stick your materials together for a strong, permanent bond.



Technical Documents



View this product online at https://marathonhardware.com/pd/F2P10SOLO



Technical Documents

5016 Pacific Highw Ferndale, WA98244		Profe	ssional Wood Formula
Phone: 1-888-443- Fax: 1-360-650-107	3748	Safety Data Sheet	
142.1-300-030-107	, <u>,</u>	according to Regulation (EC) No 1907/2006	
		2P-10 Activator	
Print date: 05.17.2018		2P-10 Activator	Page 1 of 1
SECTION 1: Identifica	ation of the	e substance/mixture and of the company/ur	ndertaking
1.1. Product identifier 2P-10 Activator			
1.2. Relevant identified	uses of the	substance or mixture and uses advised against	1
Use of the substance Industrial and profe			
Uses advised against any non-intended u			
1.3. Details of the suppli	ier of the s		
Company name:		FastCap LLC	
Place: Telephone:		5016 Pacific Highway Ferndale, WA 98248	
Internet:		+1 360-752-2138 www.fastcap.com	
Responsible Departme	ent:	info@fastcap.com	
1.4. Emergency telephon number:	ne	Chemtrec 1-800-262-8200	
SECTION 2: Hazards 2.1. Classification of the Regulation (EC) No. 12 Hazard categories:	e substance 272/2008	e or mixture	
2.1. Classification of the Regulation (EC) No. 12 Hazard categories: Flammable liquid: Serious eye damag Specific target org Hazard Statements Highly flammable li Causes serious ey	e substance 272/2008 : Flam. Liq. 2 ge/eye irrital an toxicity - 5: iquid and va re irritation.	tion: Eye Imit. 2 single exposure: STOT SE 3 pour.	
2.1. Classification of the Regulation (EC) No. 12 Hazard categories: Flammable liquid: I Serious eye damag Specific target org: Hazard Statements Highly flammable li Causes serious ey May cause drowsin	e substance 272/2008 : Flam. Liq. 2 ge/eye irrital an toxicity - 5: iquid and va re irritation.	tion: Eye Imit. 2 single exposure: STOT SE 3 pour.	
2.1. Classification of the Regulation (EC) No. 12 Hazard categories: Flammable liquid: I Serious eye damag Specific target orgs Hazard Statements Highly flammable li Causes serious ey May cause drowsin 2.2. Label elements	e substance 272/2008 : Flam. Liq. 2 ge/eye irrital an toxicity - s: iquid and va e irritation. ness or dizz	tion: Eye Imit. 2 single exposure: STOT SE 3 pour.	
2.1. Classification of the Regulation (EC) No. 12 Hazard categories: Flammable liquid: I Serious eye damag Specific target orgi Hazard Statements Highly flammable i Causes serious ey May cause drowsir 2.2. Label elements Regulation (EC) No. 12 Hazardous compone	Plan. Liq. 2 ge/eye irrital an toxicity - s: iguid and va re irritation. ness or dizz	tion: Eye Imit. 2 single exposure: STOT SE 3 pour.	
2.1. Classification of the Regulation (EC) No. 12 Hazard categories: Flammable liquid : Serious eye damag Specific target orga Hazard Statements Highly flammable in Causes serious eye May cause drowsin 2.2. Label elements Regulation (EC) No. 12 Hazardous compone Acetone	e substance 272/2008 : Flam. Liq. 2 ge/eye irrital an toxicity - s: iquid and va e irritation. ness or dizz 272/2008 ints which r	e or mixture tion: Eye Imit. 2 single exposure: STOT SE 3 ipour.	
2.1. Classification of the Regulation (EC) No. 12 Hazard categories: Flammable liquid: I Serious eye damag Specific target orgi Hazard Statements Highly flammable i Causes serious ey May cause drowsir 2.2. Label elements Regulation (EC) No. 12 Hazardous compone	Plan. Liq. 2 ge/eye irrital an toxicity - s: iguid and va re irritation. ness or dizz	e or mixture tion: Eye Imit. 2 single exposure: STOT SE 3 ipour.	
2.1. Classification of the Regulation (EC) No. 12 Hazard categories: Flammable liquid: I Serious eye dama Specific target org: Hazard Statements Highly flammable i Causes serious ey May cause drowsir 2.2. Label elements Regulation (EC) No. 12 Hazardous compone Acetone Signal word: Pictograms:	e substance 272/2008 : Flam. Liq. 2 ge/eye irrital an toxicity - s: iquid and va e irritation. ness or dizz 272/2008 ints which r	e or mixture tion: Eye Imit. 2 single exposure: STOT SE 3 ipour.	
2.1. Classification of the Regulation (EC) No. 12 Hazard categories: Flammable liquid: I Serious eye damag Specific target orgs Hazard Statements Highly flammable li Causes serious ey May cause drowsin 2.2. Label elements Regulation (EC) No. 12 Hazardous compone Acetone Signal word: Pictograms: Hazard statements	e substance 272/2008 Flam. Liq. 2 gefeye irritat an toxicity - 5: liquid and va e irritation. ness or dizz 272/2008 nts which r Danger	tion: Eye Imit. 2 single exposure: STOT SE 3 pour. iness. must be listed on the label	
2.1. Classification of the Regulation (EC) No. 12 Hazard categories: Flammable liquid: I Serious eye dama Specific target org: Hazard Statements Highly flammable i Causes serious ey May cause drowsir 2.2. Label elements Regulation (EC) No. 12 Hazardous compone Acetone Signal word: Pictograms:	e substance 272/2008 : Flam. Liq. 2 geleye irritation. ness or dizz 272/2008 mts which r Danger Highly fla Causes 1	e or mixture tion: Eye Imit. 2 single exposure: STOT SE 3 ipour.	
2.1. Classification of the Regulation (EC) No. 12 Hazard categories: Flammable liquid: 1 Serious eye dama Specific target org Hazard Statements Highly flammable ii Causes serious ey May cause drowsir 2.2. Label elements Regulation (EC) No. 12 Hazardous compone Acetone Signal word: Pictograms: Hazard statements H225 H319	e substance 272/2008 : Flam. Liq. 2 geleye irritat an toxicity - 5 : iguid and va e irritation. ness or dizz 272/2008 ints which r Danger Highly fla Causes f May cau nents Keep aw	e or mixture iion: Eye Imit. 2 single exposure: STOT SE 3 ipour. iness. must be listed on the label v v v v v v v v v v v v v v v v v v v	d other ignition sources. No
2.1. Classification of the Regulation (EC) No. 12 Hazard categories: Flammable liquid: 1 Serious eye dama Specific target org Hazard Statements Highly flammable li Cause serious ey May cause drowsin 2.2. Label elements Regulation (EC) No. 12 Hazardous compone Acetone Signal word: Pictograms: Hazard statements H225 H319 H336 Precautionary statem	e substance 272/2008 Flam. Liq. 2 geleye irritation. ness or dizz 272/2008 ints which r Danger Highly fit Causes is May cau- ments Keep aw smoking. Call a P	e or mixture iion: Eye Imit. 2 single exposure: STOT SE 3 ipour. iness. must be listed on the label v v v v v v v v v v v v v v v v v v v	d other ignition sources. No

View this product online at https://marathonhardware.com/pd/F2P10SOLO



Technical Documents

Revision Date 10/11/19 Page 1/1 1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY UNDERTAKING 1.1. Product identifier	ne: 1-888-443-3748 1-360-650-1075	Safety Data Sheet	
UNDERTAKING 1.1. Product identifier Product name 2P-10 SOLO THICK 2 O / 2P-10 THICK 10 OZ / 2P-10 RT THICK 2.25 / 2P-10 THICK 10 OZ / 2P-10 KIT / 2P-10 SOLOKIT Product Grade 2P-10 THICK Product Grade 2P-10 THICK CAS number 7085-85-0 EC number 203-91-5 REACH number 01-2119527766-29-0001 1.2. Relevant identified uses of the substance and uses advised against Applications Industrial adhesives application Consumer use of adhesives 1.3. Details of the supplier of the safety data sheet Name FastCap LLC Address Address 5016 Pacific Highway Ferndale, WA 98248 USA Telephone 1-360-752-2138 Fax 1-360-650-1075 Contact email info@fastcap.com 1.4. Emergency telephone number Chemtrec Telephone 1-800-262-8200 1.400-262-8200			
Product name 2P-10 SOLO THICK 2 O / 2P-10 THICK 10 OZ / 2P-10 RT THICK 2.25 / 2P-10 THICK 10 OZ / 2P-10 KTT / 2P-10 SOLOKIT Product Grade 2P-10 THICK CAS number 7085-85-0 EC number 230-391-5 REACH number 01-2119527766-29-0001 12. Relevant identified uses of the substance and uses advised against Applications Industrial adhesives application Consumer use of adhesives Consumer use of adhesives 13. Details of the supplier of the safety data sheet Name Name FastCap LLC Address 5016 Pacific Highway Ferndale, WA 98248 USA USA Telephone 1-360-752-2138 Fax 1-360-650-1075 Contact email info@fastcap.com 1.4. Emergency telephone number 1-800-262-8200			
Product name 2P-10 SOLO THICK 2 O / 2P-10 THICK 10 OZ / 2P-10 RT THICK 2.25 / 2P-10 THICK 10 OZ / 2P-10 KIT / 2P-10 SOLOKIT Product Grade 2P-10 THICK CAS number 7085-85-0 EC number 230-391-5 REACH number 01-2119527766-29-0001 12. Relevant identified uses of the substance and uses advised against Applications Applications Industrial adhesives application Consumer use of adhesives 13. Details of the supplier of the safety data sheet Name Name FastCap LLC Address 5016 Pacific Highway Ferndale, WA 98248 USA USA Telephone 1-360-752-2138 Fax 1-360-650-1075 Contact email info@fastcap.com 14. Emergency telephone number Chemtrec Telephone 1-800-262-8200	.1. Product identifier		
CAS number 7085-85-0 EC number 230-391-5 REACH number 01-2119527766-29-0001 1.2. Relevant identified uses of the substance and uses advised against Applications Applications Industrial adhesives application Consumer use of adhesives 1.3. Details of the supplier of the safety data sheet Name Name FastCap LLC S016 Pacific Highway Ferndale, WA 98248 USA Telephone 1-360-752-2138 I Fax Fax 1-360-650-1075 Contact email Construct email info@fastcap.com 1.4. Emergency telephone number Chemtrec Telephone 1-800-262-8200		2P-10 SOLO THICK 2 O / 2P-10 THICK 10 OZ / 2P-10 RT THICK 2.25 / 2P-10 RT THICK 10 OZ / 2P-10 KIT / 2P-10 SOLOKIT	
EC number 230-391-5 REACH number 01-2119527766-29-0001 1.2. Relevant identified uses of the substance and uses advised against Applications Applications Industrial adhesives application Consumer use of adhesives Consumer use of adhesives 1.3. Details of the supplier of the safety data sheet Name Name FastCap LLC Address S015 Pacific Highway Ferndale, WA 98248 USA Telephone 1-360-752-2138 Fax 1-360-650-1075 Contact email info@fastcap.com 1.4. Emergency telephone number 1-800-262-8200	Product Grade	2P-10 THICK	
REACH number 01-2119527766-29-0001 1.2. Relevant identified uses of the substance and uses advised against Applications Industrial adhesives application Consumer use of adhesives 1.3. Details of the supplier of the safety data sheet Name FastCap LLC Address 5016 Pacific Highway Ferndale, WA 98248 USA Telephone 1-360-752-2138 Fax 1-360-650-1075 Contact email info@fastcap.com 1.4. Emergency telephone number Chemtrec Telephone 1-800-262-8200	CAS number	7085-85-0	
1.2. Relevant identified uses of the substance and uses advised against Applications Industrial adhesives application Consumer use of adhesives 1.3. Details of the supplier of the safety data sheet Name FastCap LLC Address 5016 Pacific Highway Ferndale, WA 98248 USA Telephone 1-360-752-2138 Fax 1-360-650-1075 Contact email info@fastcap.com 1.4. Emergency telephone number 1-800-262-8200	EC number	230-391-5	
Applications Industrial adhesives application Consumer use of adhesives 1.3. Details of the supplier of the safety data sheet Name FastCap LLC Address 5016 Pacific Highway Ferndale, WA 98248 USA Telephone 1-360-752-2138 Fax 1-360-650-1075 Contact email info@fastcap.com 1.4. Emergency telephone number Chemtrec Telephone 1-800-262-8200	REACH number	01-2119527766-29-0001	
Name FastCap LLC Address 5016 Pacific Highway Ferndale, WA 98248 USA Telephone 1-360-752-2138 Fax 1-360-650-1075 Contact email info@fastcap.com 14. Emergency telephone number 1-800-262-8200		Industrial adhesives application	
Fax 1-360-650-1075 Contact email info@fastcap.com L4. Emergency telephone number 1-800-262-8200	Name	FastCap LLC 5016 Pacific Highway Ferndale, WA 98248	
Contact email info@fastcap.com 1.4. Emergency telephone number Chemtrec Telephone 1-800-262-8200	Telephone	1-360-752-2138	
1.4. Emergency telephone number Chemtrec Telephone 1-800-262-8200	Fax	1-360-650-1075	
Chemtrec Telephone 1-800-262-8200	Contact email	info@fastcap.com	
2. HAZARDS IDENTIFICATION			
	. HAZARDS IDENTIFIC	ATION	
2.1. Classification of the substance	.1. Classification of the substa	nce	
2.1.1. Classification of the product according to DSD (67/548/EC) Xi IRRITANT R 36/37/38 Irritating to eyes, respiratory system and skin			
2.1.2. Classification of the product according to CLP (1272/2008/EC) Eye irrit. 2 H319 Causes serious eye irritation			
STOT SE 3 H335 May cause respiratory irritation	STOT SE 3	H335 May cause respiratory irritation	
Skin irrit. 2 H315 Causes skin irritation		H315 Causes skie initiation	

View this product online at https://marathonhardware.com/pd/F2P10SOLO